

INON

INON M67 Lens Holder DP-S / M67 Lens Holder DP for Float Arm

Thank you for purchasing INON product.

INON M67 Lens Holder DP is attached on compatible strobe arm/Grip Base to carry M67 Mount series attachment lens to help easy and speedy lens replacement underwater.

Features

- M67/pitch0.75 screw mount (M67 Mount) compatible. Carries INON M67 Mount series lens on compatible Arm body/Grip Base etc.
- M67 Lens Holder DP series can carry "UFL-M150 ZM80" and "UWL-S100 ZM80" as well as M67 Mount series lenses.

- Package contents :**
- M67 Lens Holder [screw] ① ×1 (DP-S* only)
 - M67 Lens Holder [hole] ② ×1 (DP-F* only)
 - Lens Holder Base ③ ×1 (DP-S * only)
 - Thumb Knob Screw ④ ×1 (DP-S * only)
 - Allen Wrench ⑤ ×1 (DP-F * only)
 - This user manual ×1



**DP-S" stands for "M67 Lens Holder DP-S",
and "DP-F" for "M67 Lens Holder DP for Float Arm"

- Compatible lens/ accessory** : (as of February 2015)
- INON 「UFL-M150 ZM80」 Underwater Micro Fisheye Lens + 「M27-M67 Mount Converter for UFL-M150 ZM80」
 - INON 「UWL-S100 ZM80」 Wide Conversion Lens + 「M52-M67 Mount Converter for UWL-S100 ZM80」
 - INON 「UWL-100 Achromat Type1/Type2」 Wide Conversion Lens
 - INON 「UWL-H100 28M67 Type1/Type2」 Wide Conversion Lens
 - INON 「UCL-165M67」 「UCL-330」 「UCL-100M67」 Close-up Lens

- Compatible arm** : (as of February 2015)
- M67 Lens Holder DP type differs among different strobe arm/Grip Base etc. to use.
Please check if your M67 Lens Holder DP is compatible with your strobe arm/Grip Base etc. before installation.

● M67 Lens Holder DP-S compatible products

- INON Grip Base DII with Rubber Grip D, Grip Base DIII with Rubber Grip D
- INON D Holder Extension Bar + Grip Base D4/Grip Base M1/D Holder
- INON Arm body(SS/S/M/L), YS Arm body(MS/M)

● M67 Lens Holder DP for Float Arm compatible products

- INON Float Arm body(S/M/ML), Mega Float Arm body(S/M)
- INON M5 Joint + Stick Arm body(SS/S/M/L)
- INON M5 Joint + Multi Arm body(ML/L/LL/XL)

● Compatible products to be sandwiched between M67 Lens Holder DP [screw] and M67 Lens Holder DP [hole]

- INON Arm body(SS/S/M/L) , YS Arm body(MS/M)

Any of compatible arm can be sandwiched between M67 Lens Holder DP [screw] and M67 Lens Holder DP [hole]. (It is also possible to mix with INON M67 Lens Holder series.)
To assemble this combination, **optional Cap Screw packaged with "M67 Lens Holder W"** is required.

How to install : ① Attach 「M67 Lens Holder DP-S」 on Grip Base DII/DIII, Arm Body, YS Arm Body

Attach the M67 Lens Holder [screw] and the Lens Holder Base on compatible arm as shown in images below so that the arm seats in groove between the lens holder and the base. *INON logo on the Lens Holder Base must face you (center image). Then fix them by the Thumb Knob Screw (right image).



(How to install) : ② Attach 『M67 Lens Holder DP-S』 on 『D Holder Extension Bar』 + compatible products

Refer to 『D Holder Extension Bar』 user manual for detail of installation and usage.

③ Attach 『M67 Lens Holder DP for Float Am』 on Float Arm Body or Mega Float Arm Body

Attach the M67 Lens Holder [hole] on compatible product as shown in **image [left]** below so that the Lens Holder base on the compatible product seats in groove of the M67 Lens Holder [hole]. Then fix it by the Cap Screw supplied with compatible product (center image).

DO NOT use any other cap screw comes with other products or compatible products will be damaged.
DO NOT tighten too much to avoid accidental damage on the M67 Lens Holder.



Maximum two M67 Lens Holder [hole] can be attached on Float Arm/Mega Float Arm as they have Lens Holder bases on both sides.

④ Attach 『M67 Lens Holder DP for Float Arm』 on 『M5 Joint』 + compatible products

Refer to 『M5 Joint』 user manual for detail of installation and usage.

⑤ Attach M67 Lens Holder [screw] and M67 Lens Holder [hole] on Arm Body, YS Arm Body

Attach the M67 Lens Holder [screw] and the M67 Lens Holder [hole] on compatible arm as shown in images below so that the arm seats in groove between the two parts. *M67 Lens Holder [hole] must face you. Then fix them with the Cap Screw (cap screw supplied with the M67 Lens Holder W) by using supplied Allen Wrench. **DO NOT tighten too much to avoid damage on the M67 Lens Holder.**



How to attach compatible lens : Follow same procedure to attach the lens on a water-proof protector equipped with M67/pitch 0.75 screw mount or M67 Mount Base. Refer to M67 mount series lens user manual for detail. Apply little amount of grease (grease for housing) on threaded part of M67 Lens Holder to prevent 「salt build-up」 or 「electrical corrosion」 between M67 Lens Holder and M67 Mount series lens.

Maximum mountable number of this unit per compatible product : (as of February 2015)

Combined product	One side	Both sides mount compatibility	Total
Grip Base D II / Grip Base D III	1	No	1
Grip Base D4(*1)	1	No	1
Grip Base M1(*1)	1	No	1
D Holder(*1)	1	No	1
Arm SS/S Body	1	Yes	2
Arm M Body	2	Yes	4
Arm L Body	3	Yes	6
YS Arm MS Body	1	Yes	2
YS Arm M Body	2	Yes	4

Combined product	One side	Both sides mount compatibility	Total
Float Arm S/M/ML Body	1	Yes	2
Mega Float Arm S/M Body	1	Yes	2
Stick Arm SS/S/M Body (*2)	1	No	1
Stick Arm L Body (*2)	3	No	3
Multi Ball Arm ML/L Body (*2)	1	No	1
Multi Ball Arm LL/XL Body (*2)	3	No	3

(*1) When used in combination with 『D Holder Extension Bar』

(*2) When used in combination with 『M5 Joint』

INON Inc. 2-18-9, Dai, Kamakura, Kanagawa 247-0061
 E-mail support@inon.co.jp / Fax. +81(0)467-48-2178
 URL <http://www.inon.jp/>

February, 2015