

INON

INON M52 Lens Holder for Float Arm / M52 Lens Holder S / M52 Lens Holder W

Thank you for purchasing INON product.

INON *M52 Lens Holder* is attached on compatible INON arm to carry M52 Mount series attachment lens to help easy and speedy lens replacement underwater.

Features

- M52/pitch0.75 screw mount (M52 Mount) compatible. Carries INON M52 Mount series lens on compatible arm/Grip Base etc.
- Besides M52 mount lens, M52 Lens Holder series can carry *UFL-M150 ZM80* attached on the *Step-up Ring 52-67* as well.

Package contents :

- M52 Lens Holder [hole] ① ×1 (F/W* only)
- M52 Lens Holder [screw] ② ×1 (S/W* only)
- Lens Holder Base ③ ×1 (S/W* only)
- M5 x 18 Thumbscrew ④ ×1 (S/W* only)
- M5 x 15 Cap Screw ⑤ ×1 (W* only)
- Allen Wrench (WAF:4 mm) ⑥ ×1 (W/F* only)
- This user manual ×1

* "F" stands for "M52 Lens Holder for Float Arm",
"W" for "M52 Lens Holder W" and "S" for "M52 Lens Holder S"



Compatible lens/ accessory (as of April 2020)

- INON *UWL-95 C24 M52* Wide Conversion Lens
- INON *UFL-M150 ZM80* Underwater Micro Fisheye Lens + *M27-M67 Mount Converter for UFL-M150 ZM80* + *Step-up Ring 52-67*

Compatible arm (as of April 2020) : Compatible *M52 Lens Holder* type differs among different arm/Grip Base etc. to use with. Please check if your *M52 Lens Holder* is compatible with your arm/Grip Base etc. before installation.

● M52 Lens Holder for Float Arm compatible products

- INON *Float Arm body (S/M/ML)*, *Mega Float Arm body (S/M)*
- INON *Mega Float Tube (S/M)* attached on INON *Carbon Telescopic Arm (SS/S/M/L)*
- INON *M5 Joint* attached on *Stick Arm body (SS/S/M/L)*
- INON *M5 Joint* attached on *Multi Ball Arm body (ML/L/LL/XL)*

● M52 Lens Holder S compatible products


- INON *Grip Base DII with Rubber Grip D*, *Grip Base DIII with Rubber Grip D*
- INON *D Holder Extension Bar* attached on *Grip Base D4/Grip Base M1/D Holder*
- INON *Arm body (SS/S/M/L)*, *YS Arm body (MS/M)*

● M52 Lens Holder W compatible products

- INON *Arm body (SS/S/M/L)*, *YS Arm body (MS/M)*

How to install : ① **When installing M52 Lens Holder for Float Arm on Float Arm Body/Mega Float Arm Body/Mega Float Tube**
Attach the *M52 Lens Holder [hole]* on compatible product as shown in **below left image** so that the Lens Holder base on the compatible product seats in the groove on the back of the *M52 Lens Holder [hole]*. Then fix it by the Cap Screw supplied with compatible product (**center image**).


DO NOT use any other cap screw other than the cap screw supplied with compatible product or compatible products will be damaged. DO NOT tighten too much to avoid accidental damage on the M52 Lens Holder.



Lens Holder base



Use this Cap Screw DO NOT USE




Supplied cap screw with compatible product Other cap screw

Maximum two *M52 Lens Holder [hole]* can be attached on *Float Arm/Mega Float Arm* as they have Lens Holder bases on both sides.


- ② **When installing M52 Lens Holder for Float Arm on M5 Joint attached on compatible products**
Refer to *M5 Joint* user manual for detail of installation and usage.

- ③ **When installing M52 Lens Holder S on Grip Base DII/DIII, Arm Body, YS Arm Body**
Attach the *M52 Lens Holder [screw]* and the *Lens Holder Base* on compatible product as shown in images below so that the arm seats in groove between the *M52 Lens Holder [screw]* and the *Lens Holder Base*. *INON logo on the *Lens Holder Base* has to be facing you (center image). Then fix them by the thumbscrew (right image).



- ④ **When installing M52 Lens Holder S on D Holder Extension Bar attached on compatible products**
Refer to *D Holder Extension Bar* user manual for detail of installation and usage.

- ⑤ **When installing M52 Lens Holder W on Arm Body, YS Arm Body**
Attach the *M52 Lens Holder [screw]* and the *M52 Lens Holder [hole]* on compatible arm as shown in images below so that the arm seats in groove between the two parts. **M52 Lens Holder [hole]* has to be facing you. Then fix them with the Cap Screw (cap screw supplied with the *M52 Lens Holder W*) by using supplied Allen Wrench. **DO NOT overtighten to avoid damage on the M52 Lens Holder.**



How to attach compatible lens

- : Follow same procedure to attach the lens on a underwater housing equipped with M52/pitch 0.75 screw mount. Refer to M52 mount series lens user manual for detail. Apply little amount of grease (grease for housing) on threaded part of M52 Lens Holder to prevent salt build-up or electrical corrosion between *M52 Lens Holder* and M52 Mount series lens.

INON Inc.

2-18-9, Dai, Kamakura,
Kanagawa 247-0061 JAPAN
E-mail support@inon.co.jp
Fax. +81(0)467-48-2178
URL <http://www.inon.jp/>

April 2020