

INON

INON Red Filter LE INON W40° Filter LE INON W50° Filter LE

Thank you for purchasing INON product.

INON Filter LE series provides additional features for compatible INON LED flashlight, INON “Diffuser 2” series and INON “Color Temperature Conversion Filter” series.

- Function** :
- **Red Filter LE ①**
 - 1) Suppress influence of light on shy subjects.
 - 2) Prevents Focus Light influence when Z-240/D-2000 operates S-TTL auto exposure for super macro subject (shooting distance is 5cm/2” or less and distance between a strobe and subject is 10cm/4” or less) to support precise and accurate S-TTL auto exposure control. Refer to user manual of Z-240/D-2000 strobe for detail of S-TTL auto.

The Red Filter LE is underwater use ONLY. Not usable on land.

- **W40° Filter LE ②** *Not compatible with the LE330h/LE350/LE350 Type2/LE550-S/LE600h-S/
LE700-S/LE700-S Type2/LE700-W/LE700-W Type2
 - 3) Effectively diffuse LED flashlight/strobe built-in Focus Light to provide natural and seamless wide LED light (approx. 40°).
- **W50° Filter LE ③** *Not compatible with the LE600h-W/LE700-W/LE700-W Type2
 - 4) Effectively diffuse LED flashlight/strobe built-in Focus Light to provide natural and seamless wide LED light (approx. 50° with LE250/LE240/strobe built-in Focus Light, 65° with LE550-S, and 60° with LE350/LE350 Type2/LE700-S/LE700-S Type2) which is ideal as close range fill-in light for photography.

- Compatible product:**
- LE250 (*1)
 - LE240 (*1)
 - LE330h (*4)
 - LE350/LE350 Type2 (*4)
 - LE550-S (*2)
 - LE600h-S (*4)
 - LE600h-W (*5)
 - LE700-S/LE700-S Type2 (*4)
 - LE700-W/LE700-W Type2 (*5)
 - Color Temperature Conversion Filter(4900K) (*1)
 - Color Temperature Conversion Filter(4600K) (*1)
 - -0.5 White Diffuser 2 (External Auto) (*1)
 - -0.5 Blue Diffuser 2 (External Auto) (*1)
 - -1.5 White Diffuser 2 (External Auto) (*1)
 - -1.5 Blue Diffuser 2 (External Auto) (*1)
 - -0.5 White Diffuser 2 (TTL/Manual) (*1)
 - -0.5 Blue Diffuser 2 (TTL/Manual) (*1)
 - -0.5 (4900K) Diffuser 2 (TTL/Manual) (*1)
 - -0.5 (4600K) Diffuser 2 (TTL/Manual) (*1)
 - -1.5 White Diffuser 2 (TTL/Manual) (*1)
 - -1.5 Blue Diffuser 2 (TTL/Manual) (*1)
 - -0.5 White Diffuser 2 bundled with Z-240 strobe. (*3)



- *1) Red Filter LE/W40° Filter LE are packaged.
- *2) Red Filter LE is packaged. Not compatible with W40° Filter LE.
- *3) Red Filter LE/W40° Filter LE are packaged with the Z-240 from July 2009 production.
- *4) Red Filter LE/W50° Filter LE are packaged. Not compatible with W40° Filter LE.
- *5) Red Filter LE is packaged. Not compatible with W40° Filter LE/W50° Filter LE.

- How to Attach** :
- Screw a Filter straight in the threads of a “Light Head” of compatible LED Light or Focus Light Window on “Diffuser 2”/“Color Temperature Conversion Filter”.
Make sure to screw in straight to prevent accidental damage on thread part of a Filter, “Diffuser 2” or “Color Temperature Conversion Filter”.



INON INC.

2-18-9 Dai, Kamakura, Kanagawa 247-0061 JAPAN
E-mail / Fax. support@inon.co.jp / +81(0)467-48-2178
URL / http://www.inon.jp/

As of November 2020