

# INON SYSTEM TABLE for X-2 HOUSING (for Canon EOS Full-Frame Model)

## Lens Compatibility (current model)

Canon Zoom Lens	Port/Extension Ring	Gear/MRS Ring
EF8-15mm F4L Fisheye USM	Dome Port 2+Shade 2 Set <sup>*6</sup> + Extension Ring 18	Zoom Gear 8-15
	Dome Port 115 <sup>*6</sup> + Extension Ring 18	
EF16-35mm F4L IS USM <sup>*4</sup>	Dome Port 2+Shade 2 Set + Extension Ring M + Extension Ring 36	Zoom Gear EF16-35F4L
	Dome Port 115 Extension Ring M + Extension Ring 36	

Tokina Zoom Lens	Port/Extension Ring	Gear/MRS Ring
AT-X 107 DX Fisheye <sup>*7</sup>	Dome Port 2+Shade 2 Set + Extension Ring S	Zoom Gear AT-X107
AT-X 107 NH Fisheye hood removed <sup>*7*8</sup>	Dome Port 115 + Extension Ring S	
	Dome Port 2+Shade 2 Set + Extension Ring S	

Canon Single Focal Lens	Port/Extension Ring	Gear/MRS Ring
EF20mm F2.8 USM <sup>*1</sup>	Dome Port 2+Shade 2 Set + MF EXT. Ring M (w/o control ring) <sup>*2</sup>	Focus Gear 20-100
	MF Wide Port (w/o control ring)	

Canon Macro Lens	Port/Extension Ring	Gear/MRS Ring
EF100mm F2.8L Macro IS USM	MRS100 Port Type U III	MRS Magnet Ring
	MRS100 Port Type U III (w/o control ring) <sup>*3</sup>	N/A
	MRS100 Port Type U II + Extension Ring S	MRS Magnet Ring
	MRS100 Port Type U II (w/o control ring) <sup>*3</sup> + Extension Ring S	N/A
EF100mm F2.8 Macro USM	MRS100 Port Type U II	MRS Magnet Ring
	MRS100 Port Type U II (w/o control ring) <sup>*3</sup>	N/A
EF180mm F3.5L Macro USM	MRS100 Port Type S + Extension Ring M	MRS Magnet Ring

## Telconverter/Extender Compatibility (current model)

Kenko Teleconverter	Compatible Lens	Required Extension Ring
TELEPLUS HD DGX 1.4X Canon EOS	EF100mm F2.8L Macro IS USM	Extension Ring 18
	EF100mm F2.8 Macro USM	
	EF180mm F3.5L Macro USM	
TELEPLUS HD DGX 2.0X Canon EOS	EF100mm F2.8L Macro IS USM	Extension Ring 36
	EF100mm F2.8 Macro USM	
	EF180mm F3.5L Macro USM	

## Lnes Compatibility (discontinued model)

Canon Zoom Lens	Port/Extension Ring	Gear/MRS Ring
EF16-35mm F2.8L II USM *4	Dome Port 2+Shade 2 Set + Extension Ring M + Extension Ring 36	Zoom Gear 8-15
	Dome Port 115 Extension Ring M + Extension Ring 36	
EF20-35mm F3.5-4.5 USM *1	MF Wide Port (w/o control ring)	Focus Gear 20-100 *5
EF22-55mm F4-5.6 USM	MF Wide Port (w/o control ring)	Zoom Gear 28-90USM
EF28-80mm F3.5-5.6 II USM	MF Standard Port 2(w/o control ring)	
EF28-80mm F3.5-5.6 III USM		
EF28-80mm F3.5-5.6 IV USM		
EF28-80mm F3.5-5.6 V USM		
EF28-90mm F4-5.6 USM		
EF35-80mm F4-5.6 USM		

Canon Single Focal Lens	Port/Extension Ring	Gear/MRS Ring
EF15mm F2.8 Fisheye	Dome Port 2+Shade 2 Set	Focus Gear 15-50
EF24mm F2.8 *9	MF Flat Port(w/o control ring)	Focus Gear 15-50
EF28mm F2.8 *1*9		
EF35mm F2 *9		

Canon Macro Lens	Port/Extension Ring	Gear/MRS Ring
EF50mm F2.5 Compact Macro	MF Std. Port II (w/o control ring)	Focus Gear 15-50
EF100mm F2.8 Macro *9	MRS100 Port Type S	MRS Magnet Ring 100S Set (Set of MRS Magnet Ring and MRS Magnet Ring 100S Adapter)

## Telconverter/Extender Compatibility (discontinued model)

Kenko Teleconverter	Compatible Lens	Required Extension Ring
TelePlus MC7 AF 2.0X DGX for Canon EOS	EF100mm F2.8L Macro IS USM	Extension Ring 36
	EF100mm F2.8 Macro USM	
	EF100mm F2.8 Macro * <sup>9</sup>	
	EF180mm F3.5L Macro USM	
1.5X Teleplus MC4 DG for Canon EOS	EF100mm F2.8 Macro USM	Extension Ring 18
	EF100mm F2.8 Macro * <sup>9</sup>	
	EF180mm F3.5L Macro USM	
2X Teleplus MC7 DG for Canon EOS	EF100mm F2.8 Macro USM	Extension Ring 36
	EF100mm F2.8 Macro * <sup>9</sup>	
	EF180mm F3.5L Macro USM	
3XM Teleplus PRO 300 for Canon EOS	EF100mm F2.8 Macro USM	Extension Ring L
	EF100mm F2.8 Macro * <sup>9</sup>	
	EF180mm F3.5L Macro USM	
1.5X Teleplus SHQ for Canon EOS	EF100mm F2.8 Macro USM	Extension Ring 18
	EF100mm F2.8 Macro * <sup>9</sup>	
	EF180mm F3.5L Macro USM	
2X Teleplus MC7 for Canon EOS	EF100mm F2.8 Macro USM	Extension Ring 36
	EF100mm F2.8 Macro * <sup>9</sup>	
	EF180mm F3.5L Macro USM	

Canon Extender	Compatible Lens	Port/Extension Ring
EXTENDER EF1.4x	EF180mm F3.5L Macro USM	MRS100 Port Type S + Extension Ring 58
EXTENDER EF2x	EF180mm F3.5L Macro USM	MRS100 Port Type S + Extension Ring 81

- \*1 When shooting with wider aperture setting, image quality may degrade on peripheral part. Use smaller aperture setting.
- \*2 Minimum focus distance gets little bit longer. Commercially available close-up lens No.2 like "Canon Close-up Lens 500D/72mm" etc. would be recommended to attach on lens front to compensate it.
- \*3 Auto focus (AF) only. For manual focus operation, optional "MRS Control Ring 100U II /100U III /50 for Olympus" and compatible "Magnet Ring" is necessary.
- \*4 When shooting with zoom wide end with wider aperture setting, peripheral part of an image may get degraded. Use smaller aperture setting.
- \*5 Supports zoom operation. Manual focus (MF) is not supported and only auto focus shooting is available.
- \*6 Remove the protector when shooting at wide end (8mm) for circular fisheye image.
- \*7 Not as recommended by the manufacture as the lens is originally designed for APS-C format cameras. Shooting at zoom wide end will have significant vignetting, so zoom in between zoom position 14.5mm - 17mm not to have vignetting.
- \*8 Zoom wide end setting won't have hood shape shadow but circular shadow will be observed.
- \*9 Non USM old style lens.

"MF Port"series ("MF Standard Port 2"/"MF Wide Port"/"MF Flat Port") or "MF EXT. Ring M" can not be attached on "Extension Ring" other than "MF EXT. Ring M".